

SIMATIC DP, 5 ELECTRON. MODULES FUER ET 200S, 4 DO SINK  
OUTPUT DC 24V/0.5A, 15 MM WIDTH, 5 PIECES PER  
PACKAGING UNIT



### Supply voltage

Reverse voltage protection Yes; when using the same load voltage as on the power module

#### Load voltage L+

- Rated value (DC) 24 V; From power module
- Reverse polarity protection Yes

### Input current

from load voltage L+ (without load), max. 5 mA; Per channel

from backplane bus 3.3 V DC, max. 10 mA

### Power loss

Power loss, typ. 0.8 W

### Address area

#### Address space per module

- with packing 4 bit
- without packing 1 byte

### Digital outputs

Number of digital outputs 4

Short-circuit protection Yes

Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	1 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	5 µA
Output delay with resistive load	
• "0" to "1", max.	300 µs
• "1" to "0", max.	600 µs
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	2 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Diagnostic functions	No
Diagnostics indication LED	
• Status indicator digital output (green)	Yes
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes

Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

**last modified:** 23.05.2016