

SIMATIC DP, 1 ELECTRON. MODULES FOR ET 200S, 8 DO SINK
OUTPUT, DC24V/0,5A, 15 MM WIDTH, 1 PIECES PER
PACKAGING UNIT



Supply voltage

Reverse voltage protection	Yes; when using the same correctly polarized load voltage as on the power module
----------------------------	----------------------------------------------------------------------------------

Load voltage L+

• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes

Input current

from load voltage L+ (without load), max.	5 mA
from backplane bus 3.3 V DC, max.	10 mA

Power loss

Power loss, typ.	1.5 W
------------------	-------

Address area

Address space per module	
• without packing	1 byte

Digital outputs

Number of digital outputs	8
Short-circuit protection	Yes

• Response threshold, typ.	1,5 A
Limitation of inductive shutdown voltage to	Typ. 47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	Max. 1 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	5 µA
Output delay with resistive load	
• "0" to "1", max.	300 µs
• "1" to "0", max.	600 µs
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Diagnostic functions	No
Diagnostics indication LED	
• Status indicator digital output (green)	Yes
Parameter	
Remark	3 byte
Potential separation	
Potential separation digital outputs	

• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

last modified: 14.05.2016