

SIMATIC DP, ELECTRON. MODULE FOR ET200SP, F-RQ
 1X24VDC/24..230VAC/5A ST, 20MM WIDTH, 1 RELAY OUTPUT (2
 NO-CONTACTS) TOTAL OUTPUT CURRENT 5A, RATED
 VOLTAGE DC 24V AND AC 24 .. 230V, USEABLE UP TO PL E
 (ISO13849-1: 2008)/ SIL 3 (IEC61508: 2010) IF CONTROLLED BY
 A F-DQ (E.G. 6ES7136-6DB00-0CA0)



General information	
Product type designation	F-RQ 1x24VDC/24 ... 230VAC/5A
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP4 and higher
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Power	
Power available from the backplane bus	100 mW
Power loss	
Power loss, typ.	1 W
Address area	
Address space per module	

• Inputs	1 byte
Digital outputs	
Number of digital outputs	1
Switching capacity of the outputs	
• with resistive load, max.	5 A
• on lamp load, max.	25 W
Switching frequency	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.1 Hz; See data in manual
• with inductive load (acc. to IEC 60947-5-1, DC13), max.	0.1 Hz
• with inductive load (acc. to IEC 60947-5-1, AC15), max.	2 Hz
Total current of the outputs (per module)	
horizontal installation	
— up to 40 °C, max.	5 A; Note derating data in the manual
— up to 50 °C, max.	4 A; Note derating data in the manual
— up to 60 °C, max.	3 A; Note derating data in the manual
vertical installation	
— up to 50 °C, max.	3 A; Note derating data in the manual
Relay outputs	
• Number of relay outputs	1; 2 NO contacts
• Rated supply voltage of relay coil L+ (DC)	24 V
• external protection for relay outputs	yes; 6 A, see data in manual
• Relay approved acc. to UL 508	Yes; Pilot Duty B300, R300
Switching capacity of contacts	
— with inductive load, max.	see additional description in the manual
— with resistive load, max.	see additional description in the manual
— Thermal continuous current, max.	5 A
— Switching current, min.	1 mA
— Switching current after exceeding 300 mA, min.	10 mA
— Switching current after exceeding 300 mA, max.	5 A
— Rated switching voltage (DC)	24 V
— Rated switching voltage (AC)	230 V
Cable length	
• shielded, max.	500 m; for load contacts
• unshielded, max.	300 m; for load contacts
• Control cable (input), max.	10 m
Interrupts/diagnostics/status information	

Diagnostics	yes, firmware update
Diagnostics indication LED	
• RUN LED	Yes; green/red DIAG LED
• Channel status display	Yes; Green LED
Potential separation	
Potential separation channels	
• between the channels	Yes; for SELV / PELV only
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
Permissible potential difference	
between channels and backplane bus/supply voltage	250 V AC (reinforced insulation)
between backplane bus and supply voltage	75 V DC/60 V AC
Isolation	
Isolation tested with	2 545 V DC/2 s (routine test)
Overvoltage category	III
tested with	
• between channels and backplane bus/supply voltage	DC 2545 V 2 s (routine test), impulse voltage test DC 7200 V / 5 positive and 5 negative pulses (type test)
• between backplane bus and supply voltage	707 V DC (type test)
Dimensions	
Width	20 mm
Weights	
Weight, approx.	56 g
last modified:	14.05.2016